

<b>Model</b>	<b>P10-1R1G-OL</b>
<b>Pixel Pitch</b>	<b>10mm</b>
<b>Module Size</b>	<b>320mm X 160mm</b>
<b>Module Resolution</b>	<b>32dots X 16dots</b>
<b>Pixel configuration</b>	<b>1R1G</b>
<b>Pixel Density</b>	<b>10000dots/m<sup>2</sup></b>
<b>Brightness</b>	<b>≥ 5500 cd/m<sup>2</sup></b>
<b>color processing</b>	
<b>refresh rate</b>	
<b>Viewing angle</b>	<b>Horizontal ≥110° Vertical ≥ 60°</b>
<b>Best Viewing distance</b>	<b>10m – 120m</b>
<b>IP rating</b>	<b>IP65</b>
<b>Continual operating period</b>	<b>□24 hours</b>
<b>Ambient temperature</b>	<b>-30°C to 60°C</b>
<b>Lifetime</b>	<b>□100,000 hours</b>
<b>Average Weight</b>	<b>55 Kg/m<sup>2</sup></b>
<b>Typical power consumption</b>	<b>350 W/m<sup>2</sup></b>
<b>Peak power consumption</b>	<b>550 W/m<sup>2</sup></b>
<b>AC voltage</b>	<b>110-240V AC 50/60Hz</b>
<b>source compatibility</b>	
<b>Control method</b>	<b>Controlled by PC</b>